# Parameterization of EPIC crop model for simulation of cotton growth in South Texas

# J. KO1\*, G. PICCINNI2, W. GUO3 AND E. STEGLICH4

 United States Department of Agriculture–Agricultural Research Service, Agricultural Systems Research Unit, 2150 Centre Avenue, Building D, Suite 200, Fort Collins, CO 80526, USA
 Monsanto Company, 700 Chesterfield Parkway West, Chesterfield, MO 63017, USA
 South Plains Precision Ag, 2810 N. Quincy, Plainview, TX 79072, USA
 Blackland Research and Extension Center, Texas A&M University, 720 East Blackland Road, Temple, TX 760502, USA

(Revised MS received 4 November 2008; First published online 15 January 2009)

## SUMMARY

Parameterization in crop simulation modelling is a general procedure to calibrate a crop model to explore the best fit for a certain regional environment of interest. The parameters of radiation use efficiency (RUE) and light interception coefficient (k) of cotton (Gossypium hirsutum) for different cultivars were estimated under various irrigation conditions in South Texas in 2006 and 2007. A calibration procedure was then performed for determination of RUE using the environmental policy impact calculator (EPIC) crop model (Williams et al. 1984). This was carried out using data sets obtained separately from the data for parameter estimation. The estimates of k and RUE were 0·63 and 2·5 g/MJ, respectively, which were determined based on the field experiment and variation of simulated lint yield. When the parameters were used with EPIC to simulate the variability in lint yields, a correlation coefficient of 0·86 and root mean square error (RMSE) of 0·22 t/ha were obtained, presenting no significant differences (paired t-test: P=0·282) between simulation and measurement. The results demonstrate that an appropriate estimate of the model parameters including RUE is essential in order to make crop models reproduce field conditions properly in simulating crop growth, yield and other variables.

### INTRODUCTION

A physiological-based description of crop growth can be explained through estimating changes in the total amount of radiation and 'the efficiency of radiation conversion to dry matter', which was defined as radiation use efficiency (RUE, g/MJ) by Monteith (1977). This concept is widely used in crop models to simulate crop dry matter accumulation. RUE can be measured as 'the slope of the regression of the gross amount of dry matter produced upon the cumulated amount of intercepted light energy' (Charles-Edwards *et al.* 1986). According to Gallagher & Biscoe (1978), RUE values for common C<sub>3</sub> plants range from 2·0 to 3·0 g/MJ, while those for C<sub>4</sub> plants range from 3·0 to

\* To whom all correspondence should be addressed. Email: Jonghan.Ko@ars.usda.gov. Previously: Texas AgriLife Research and Extension Center, Texas A&M University, 1619 Garner Field Road, Uvalde, TX 78801, USA.

4·0 g/MJ (Kiniry *et al.* 1989). RUE is influenced by the combination of light interception and the photosynthetic activity of individual leaves within the canopy, which are affected by environmental and management factors (Foale *et al.* 1984; Sinclair & Horie 1989; Rosenthal & Gerik 1991; Rosenthal *et al.* 1993).

Cotton cultivars have shown diverse growth rates, which may be attributable to differences in RUE (Rosenthal & Gerik 1991). Studies demonstrate that cotton RUE values vary, dependent upon various environmental conditions as well as cultural and management practices. Cultural practices, such as cultivar selection and plant density, were reported to affect RUE (Foale *et al.* 1984; Rosenthal & Gerik 1991; Rosenthal *et al.* 1993). Also, Sinclair & Horie (1989) reported that management practices, such as soil fertilization, could influence the differences in RUE as a result of an influence on photosynthetic activity.

Some of the reported RUE values of cotton in the USA are: 2·55 g/MJ for irrigated cv. Acala SJ-2 grown in California (Howell & Musick 1985), 2·3 g/MJ for irrigated cv. Paymaster 2326 grown in Texas High Plains (Ko *et al.* 2005) and 1·5 g/MJ for cv. Acala and 1·3 g/MJ for cv. Tamcot gown in Texas Prairies (Rosenthal & Gerik 1991).

Charles-Edwards *et al.* (1986) stated that the amount of photosynthetically active radiation (PAR) intercepted by a plant depends on leaf area distribution, which directly affects the light interception coefficient (*k*) for Beer's law. According to Monsi & Saeki (1953), *k* can be described as

$$T = I \times \exp(k \times \text{LAI}) \tag{1}$$

where T is transmitted radiation through a canopy, I is incoming radiation, and LAI is leaf area index. Kiniry *et al.* (2005) noted that reduced k values are estimated for more upright leaves and allow better light penetration into leaf canopies, eventually causing RUE to increase when biomass is source-limited. This was demonstrated by reports for peanut (Bell *et al.* 1993) and diverse  $C_4$  grasses (Kiniry *et al.* 1999). However, it has not been reported that changes in k affect the RUE values for cotton crops.

Since many crop models use RUE and k as their parameters, appropriate values of the parameters must be determined before a crop model is employed. In the present study, 2 years of diverse weather conditions in terms of rainfall were purposely chosen and RUE and k values determined for different cultivars at various irrigation regimes. To validate the parameter RUE in South Texas, crop yield was also simulated using the environmental policy impact calculator (EPIC) crop model with the RUE values determined.

## MATERIALS AND METHODS

## Field study for parameterization

Cotton was grown on an Uvalde clay soil (fine-silty, mixed, hyperthermic Aridic Calciustolls, with a pH of 8·1) during 2006 and 2007 at Texas A&M AgriLife Research Center in Uvalde, Texas (29-2175 N, 99-7572 W; 283 m asl). In 2006, six commercial cotton varieties from Bayer CropScience (Research Triangle Park, NC, USA) were planted on 11 April: ST5599, ST4892, ST4664, ST4700, ST5007 and 989B2R. Seed density was 20 647 seeds/ha with 1 m between rows; crops were harvested on 7 September. In 2007, four varieties from Bayer CropScience and Delta and Pine Land Company (Scott, MS, USA) were planted on 23 April and harvested on 17 October: ST4554, DP555, DP164 and FM9063. The varieties selected were among those best adaptable to this region from commercially available varieties for both years. After having narrow yield variations among the varieties in 2006, varieties were selected considering more various genetic pools in 2007. The experiments in both years were arranged in a split-block design with each main plot (irrigation) replicated twice and each subplot (variety) replicated three times. A  $90^{\circ}$  wedge of the centre pivot circled field (c. 4.8 ha) was divided equally into  $15^{\circ}$  irrigation regimes, which were maintained at 1.00, 0.75 and 0.50 crop evapotranspiration (ETc) values. The varieties were randomly arranged within each main plot.

Irrigation scheduling and ET regimes for the field were imposed according to daily calculations of the standardized ASCE-PM equation (ASCE-EWRI 2005). Actual crop water use requirements for cotton were determined based on the relation to a well-watered reference grass. The equation was as follows:

$$ETc = Kc \times ETo$$
 (2)

where *Kc* is the crop coefficient and ETo is the reference evapotranspiration. ET from a tall fescue grass (*Festuca arundinacea* Schreb.) with a height of 0·12 m and a surface resistance of 70 s/m was the ETo surface employed in *Kc*. The total amount of irrigation from seeding to maturity (prior to defoliation) was 487·7 mm in 2006 and 139·7 mm in 2007. During these periods, rainfall recorded was 71·4 mm in 2006 and 575·8 mm in 2007. Weather data, including rainfall and daily solar radiation (SR), were collected at a weather station 150 m from the field.

Measurements of fraction of PAR intercepted, leaf area index (LAI) and plant dry weights were taken on 11 June, 28 June, 16 July and 12 September 2007. PAR interception was measured during the growing season with a 1 m long LI-191SA line quantum sensor (LI-COR Inc., Lincoln, NE, USA). A series of measurements was taken in rapid succession, consisting of 10 PAR readings above the canopy, 10 below the canopy and 10 more above the canopy. While taking the readings below the canopy, the light sensor was moved across the plant row. Measurements were taken between 11:30 and 12:30 central daylight time during times with moderately stable incident SR. Tollenaar & Bruusema (1988) demonstrated that radiation measured near to solar noon can be representative of integrated daily radiation. The fraction of PAR intercepted was determined with the mean values of the above- and below-canopy measurements,

Destructive samples were taken of biomass accumulation in 1·0 m lengths of row on 31 May (151 days after sowing (DAS)), 20 June (171 DAS), 18 July (199 DAS) and 21 August (233 DAS) in 2006; 11 June (161 DAS), 28 June (179 DAS), 16 July (197 DAS) and 12 September (255 DAS) 2007. A representative plant was randomly selected from each sample and leaf area was measured with a LI-COR LI-3100 leaf area meter (LI-COR Inc., Lincoln, NE, USA). The plants were weighed after being dried in a forced-air




Fig. 1. Map of the region where cotton data were obtained for parameterization and simulation.

drying oven at 70 °C until the weight stabilized. Leaf area of the entire sample was calculated from the leaf area of the one plant and the ratio of the total dry weight of all plants divided by the dry weight of the one plant. Based on these techniques, values for LAI, above-ground dry weight (AGDW) and intercepted PAR were derived.

Light interception coefficients (k) were calculated from transmitted (T) and incoming (I) PAR data. Values for k were calculated for each variety as

$$k = [\ln(T/I)]/\text{LAI} \tag{3}$$

Daily radiation intercepted by the canopy was calculated from the determined k, incoming and reflected PAR, and interpolated LAI estimated between radiation measurements. Incoming PAR was assumed to be 0·45 of daily total SR (Monteith 1965; Howell *et al.* 1983; Meek *et al.* 1984). RUE was calculated from the slope of the AGDW (g/m²) as a function of accumulated intercepted PAR (MJ/m²).

## Simulation study

Two different types of field data sets were used: a set of field data collected on a research field of Texas A&M AgriLife Research Center in Uvalde, Texas, in 2003, 2004 and 2005; and a set of field data collected on farm fields at three counties of South Texas in 2006 and 2007 (Fig. 1). Cotton cultivar ST4892 (Bayer CropScience) was grown at the Research Center field for the 3 years. Cumulative growing degree days (GDD), general weather conditions and total amounts of irrigation during each crop season are summarized

in Table 1. Cotton lint yield was determined by randomly sampling and harvesting 3 m² for each plot. For the grower's field data, detailed information on each field and its cultural practices are summarized in Table 2. Cotton lint yield was determined based on the measurement of total lint harvested from each field.

The EPIC model (Williams et al. 1984) was employed in the present simulation study. EPIC includes physiologically based components to simulate erosion, plant growth and related processes. Model components include weather, hydrology, erosion, nutrient cycling, soil temperature, crop growth, tillage, pesticide fate, economics and plant environmental control. The plant growth model in EPIC (Williams et al. 1989) simulates agronomic crops, pastures and trees, with each crop having unique values for the model parameters. Values of several yield-related parameters (Wang et al. 2004) used for crop simulation in the present study are listed in Table 3. The harvest index (HI) is the ratio of economic yield to the above-ground biomass. The water stress-harvest index, PARM(3), sets the fraction of growing season when water stress starts to reduce the HI. The Soil Conservation Service (SCS) curve number index coefficient, PARM(42), regulates the effect of potential evapotranspiration in driving the SCS curve number retention parameter. The retention parameter impacts runoff volume and changes with soil water content. The differences in soil water content for each layer between field capacity and wilting point (DIFFW) impact water storage for plant use and water stress factor for crop growth.

Weather data used in the simulations were collected with a standard Campbell Scientific meteorological station (Campbell Scientific Inc., Logan, UT, USA) at each location and are available at the Texas AgriLife Research and Extension Center website (http://uvalde.tamu.edu/weather/weather.php, verified 12 November 2008). Simple linear regression and paired *t*-test were analysed using PROC REG and PROC TTEST (SAS version 9.1, Cary, NC, USA), respectively.

### RESULTS

Values of the light interception coefficient (k) obtained for different cultivars under different irrigation treatments in 2007 ranged from -0.56 to -0.72 (Fig. 2). The mean value of k determined with Eqn (3) was -0.63, which generally matched the one estimated with the relationship between fractional transmitted radiation and LAI. A k value in 2006 was determined based on the relationship between the proportion of the daily light energy intercepted by the crop canopy  $(Q_0 = 1 - e^{-k \cdot \text{LAI}})$  and k values (Fig. 3), assuming that the  $Q_0$  value agreed with the measured cotton canopy cover in the field. This estimation

Table 1. Summary of weather conditions and irrigation amounts during each cotton growing season at Texas AgriLife Research Center at Uvalde, Texas

Seeding	to maturity	CDD*	<b>A</b>	D C . II	T
Year	Date	GDD* (°C)	Average temp (°C)	Rainfall (mm)	Irrigation (mm)†
2003	02 Apr-11 Aug	1898	26.3	318.3	253.5
2004	01 Apr-16 Aug	1770	24.7	274.1	257.6
2005	07 Apr-07 Aug	1748	26.1	140.7	337.3
2006	13 Apr-20 Aug	2114	28.2	71.3	604.3
2007	16 Apr-07 Aug	1989	25.4	575.8	76.2

<sup>\*</sup> GDD, growing degree days, above a base temperature of 12 °C.

Table 2. Summarized information of farms and their cropping practices in 2006 and 2007 used in crop simulation

Year	Site	County	Latitude (N), longitude (W); elevation (m)	Soil type	Seeding to harvest	Irrigation (mm)
2006	1	Zavala	28.902, 99.568; 201	Uvalde silty clay loam	10 Apr-29 Aug	425
	2*	Uvalde	29.191, 99.855; 282	Montell clay	30 Mar-29 Aug	406
	3	Uvalde	29.293, 99.762; 302	Knippa clay	04 Apr-29 Aug	464
	4	Uvalde	29.284, 99.761; 297	Knippa clay	03 Mar-29 Aug	419
	5	Frio	28.898, 99.126; 181	Duval loamy fine sand	05 Apr-02 Sep	533
2007	6	Uvalde	29.320, 99.368; 334	Montell clay	20 Apr-10 Sep	25
	7	Uvalde	29.176, 99.760; 268	Uvalde silty clay loam	04 Apr-20 Aug	0
	8	Medina	29.375, 98.971; 309	Victoria clay	05 Apr-15 Oct	0
	9	Medina	29.397, 98.893; 251	Knippa clay	10 Apr-28 Sep	0
	10	Medina	29.335, 98.798; 213	Lewisville silty clay	26 Apr-23 Oct	76
	11	Bexar	29.333, 98.626; 208	Houston Black gravelly clay	17 Apr-01 Oct	0

<sup>\*</sup> Two fields were used from this site.

Table 3. Yield-related EPIC parameters used

Parameter	Symbol*	Value	Source of range
Harvest index	HI	0.45	J. R. Williams (personal communication)
Water stress-harvest index coefficient	PARM (3)	0.5	J. R. Williams (personal communication) and Wang <i>et al.</i> (2004)
SCS curve number index coefficient	PARM (42)	1.0	J. R. Williams (personal communication) and Wang <i>et al.</i> (2004)
Difference of soil water contents at field capacity and wilting point (/mm)	DIFFW	0.2	Morgan et al. (2003) and Wang et al. (2004)

<sup>\*</sup> Parameter symbols used in the EPIC model.

method was previously used by Ko *et al.* (2005). In the present study, the *k* estimate was c. -0.65 when the crop canopies fitted to the maximum LAI value  $(2.3 \text{ m}^2/\text{m}^2)$ .

To obtain RUE, accumulated interceptedradiation was compared with AGDW for each irrigation treatment and each cultivar (Fig. 4). As plant biomass increased, significant differences in AGDW

<sup>†</sup> Total amounts of irrigation. Irrigation rates based on in-field-calculated ETc rates.




Fig. 2. Fraction of transmitted PAR as a function of LAI and light extinction coefficients (k) for Beer's law for each cultivar using data obtained in 2007. Horizontal bars represent errors at 95% confidence interval. The empirically obtained estimate of k is presented in the table and the regression is presented for a support purpose.

were found between 1·00 and 0·50 ETc treatments as well as among the cultivars. However, there were no interactions between irrigation and cultivar, either in 2006 or 2007. Slopes of the linear relationships represent RUE values for irrigation treatments and different cultivars, showing average values of 1·5 g/MJ in 2006 and 2·2 g/MJ in 2007. RUE values in 2007 ranged from 2·0 to 2·5 g/MJ, while those in 2006 ranged from 1·3 to 2·0 g/MJ (Table 4). Since an RUE estimate is considered to be determined for crops under environmentally unperturbed conditions, the maximum value (2·5 g/MJ) found was tentatively determined as an RUE parameter of cotton grown under the South Texas conditions.

The EPIC model was then calibrated using the RUE estimates to determine an appropriate RUE value for simulation studies in South Texas. When the RUE value of 2.5 g/MJ was employed, EPIC simulated the variability in lint yields, with a correlation coefficient (r) of 0.86 and root mean square error (RMSE) of 0.22 Mg/ha (Fig. 5). While some of the farm field data points in 2007 were overestimated in simulation, paired t-tests showed that simulated yields were not significantly different from the measured yields with P = 0.282 for collective data (P =0.063 for the experimental field data from 2004 to 2005; P = 0.807 for the farm field data in 2006 and 2007). The regression line was generally close to the 1:1 line with a slope of 0.79 and  $R^2$  of 0.74. Measured yields ranged from 1.0 to 2.7 t/ha while simulated yields ranged from 1.1 to 2.5 t/ha. The upper 95% confidence interval of the regression ranged from 1.2 to 2.6 t/ha while the lower 95% confident interval ranged from 0.9 to 2.1 t/ha. Lysimeter-measured crop water use under unstressed crop conditions was previously compared with two different methods of irrigation calculation: firstly, in-field calculation with the standardized ASCE-PM formula and secondly, EPIC using the Hargreaves-Samani equation (Hargreaves & Samani 1985). This was performed as a preliminary validation of the EPIC model. No statistical difference was found between the ETc values of lysimetermeasured and the two different methods of irrigation calculation (data not shown). However, cumulative ETc varied during the growing seasons among the three methods of measurements (Fig. 6). Meanwhile, in-field calculated ETc agreed with the lysimetermeasured ETc with r value of 0.93 and RMSE of 1.34, and EPIC-Hargreaves-Samani simulated ETc agreed with lysimeter measured ETc with r value of 0.63 and RMSE of 2.76. While daily ETc rates were somewhat in general agreement between the measured and simulated values, the variations of daily cumulated ETc were within an acceptable range. In-season differences among ETc methods varied, possibly due to inexact simulation growth curves or growth stage specific crop coefficients.

# DISCUSSION

Two different k determination methods were demonstrated, one with direct measurement of the light interception by the plant canopy (Fig. 2) and the other with indirect estimation using the relationship between the proportion of the daily light energy intercepted by the crop canopy  $(Q_0 = 1 - e^{-k \cdot \text{LAI}})$  and k values (Fig. 3). However, care should be taken when the latter is employed to determine k values. Estimates can vary depending on the canopy conditions as shown for the indirectly estimated k value in 2007 (Fig. 7), which was between -0.6 and -0.7 based on the relationship between the  $Q_0$  and k values when the crop canopy fitted to the maximum LAI  $(6.5 \text{ m}^2/\text{m}^2)$ . One of the solutions for this would be to determine a k value before the plant canopy reaches full ground cover (e.g. the dotted lines in Fig. 7).

The k value determined in the present study is in agreement with the range of k value for the plants with horizontal leaves hypothesized by Rosenberg  $et\ al.$  (1983). In addition, the k value generally corresponded to the value of -0.65, used in the EPIC model (Williams  $et\ al.$  1989). On the other hand, the k value obtained in the present study was slightly higher than the values of -0.77 found by Ronsenthal & Gerik (1991) in Texas and -0.76 found by Howell & Musick (1985) in California, but generally lower than the value of -0.45, described by Jackson & Hearn (1990), grown in Texas. According to the note by Kiniry  $et\ al.$  (2005), changes of k values affect RUE values. Such a trend was reported for peanut (Bell




Fig. 3. Ratio of the daily light energy intercepted by a canopy  $(Q_0)v$ . LAI for different light extinction coefficient (k) values from -0.2 to -0.9 using data obtained in 2006. The dashed horizontal line represents the crop canopy at the maximum LAI value (the dashed vertical line).




Fig. 4. Cumulative AGDW as a function of cumulative absorbed PAR for different irrigation treatments and varieties in 2006 (a and b) and 2007 (c and d). RUEs are the slopes of the relationships: solid lines for all data (1·5 and 2·2 in 2006 and 2007, respectively) and dashed lines for smallest and largest values (detailed results presented in Table 4). Vertical bars represent errors at 95% confidence interval (n=16 and 12 for irrigation and cultivar, respectively).

Table 4. Linear relationships between cumulative AGDW and accumulated absorbed photosynthetically active-radiation (x) for different irrigation treatments and cultivars in 2006 and 2007. RUEs are the slopes of the relationships

Year	Treat	ment	Linear regression	$R^2$	
2006	Irrigation	1.00 ETc 0.75 ETc 0.50 ETc	1.8x - 21.3 1.4x + 4.81 1.4x + 8.1	1·00 0·98 0·98	
	Variety	FM989 ST4664 ST4700 ST4892 ST5007 ST5599	$   \begin{array}{c}     1 \cdot 3x + 4 \cdot 0 \\     1 \cdot 4x - 2 \cdot 3 \\     1 \cdot 7x - 12 \cdot 0 \\     1 \cdot 4x + 9 \cdot 4 \\     1 \cdot 3x + 17 \cdot 1 \\     2 \cdot 0x - 32 \cdot 9   \end{array} $	0·99 0·99 0·98 0·98 0·97 0·99	
2007	Irrigation	1·00 ETc 0·75 ETc 0·50 ETc	$2 \cdot 3x - 59 \cdot 3$ $2 \cdot 2x - 31 \cdot 1$ $2 \cdot 1x - 12 \cdot 7$	0.98 1.00 1.00	
	Variety	DP164 DP555 FM9064 ST4554	2.5x - 59.3 2.5x - 27.2 2.2x - 0.13 2.0x - 9.70	1·00 1·00 0·98 0·97	





Fig. 5. Measured v. simulated lint yield with EPIC model using data obtained at Texas AgriLife Research Center field from 2003 to 2005 and at farm fields from 2006 to 2007. Dashed lines represent the 95% confidence interval for the mean of the simulated values.

et al. 1993) and diverse  $C_4$  grasses (Kiniry et al. 1999). However, it has not been reported that changes in k affect the RUE values for cotton crops. A cotton study in Australia by Milroy & Bange (2003) also demonstrated that RUE values were not affected by the changes of k values, which ranged from -0.51 to -0.99.

The RUE values found in the present study in 2007 were within the range common for  $C_3$  plants (2.0-3.0 g/MJ; Gallagher & Biscoe 1978) and






Fig. 6. Lysimeter-measured ETc v. two methods of estimating ETc (in-field-calculated with the standardized ASCE-PM equation and EPIC-simulated using the Hargreaves–Samani equation) for cotton, Uvalde, TX, in 2006 and 2007. The in-field calculation was made using Eqn (2), i.e. ETc= $Kc \times$ ETo.

generally agreed with the cotton RUE values of 2·55 g/MJ, found by Howell & Musick (1985), and of 2·3 g/MJ, found by Ko *et al.* (2005). However, the values found in the present work in 2006 corresponded to the cotton RUE values of 1·5 and 1·3 g/MJ for each variety of the cultivars Acala and Tamcot, reported by Rosenthal & Gerik (1991). The difference of the RUE values between the 2 years in the present study can be attributed to two extreme seasonal rainfalls, 71·4 mm in 2006 and 575·8 mm in 2007. Even though irrigation was applied based on the actual crop water use requirements in both years, it is considered that plants in 2006 were grown under




Fig. 7. Ratio of the daily light energy intercepted by a canopy  $(Q_0) v$ . LAI for different light extinction coefficient (k) values from -0.2 to -0.9 using data obtained in 2007. The dashed horizontal line represents the crop canopy at the maximum LAI value (the dashed vertical line).




Fig. 8. Simulated lint yields as a function of various values of RUE. Vertical bars represent error at 95% confidence interval (n=21).

environmental stress involving water deficit in comparison with those in 2007. Similar differences were reported by Milroy & Bange (2003); depending on field conditions, RUE varied from 3·1 to 0·8 g/MJ at the same location.

Parameterization is a modelling technique that uses an empirical function to approximate the response of a physical system over a given range of environmental conditions (Huschke 1959). This technique reduces the complexity of models, simplifies the input requirement of models and makes them easier to use for operational purposes. Appropriate parameter estimation is critical to reproduce the field conditions of a crop when using crop models, including EPIC. The

traditional method of establishing the model parameter values has been through the analysis of data obtained from controlled-environment and field studies (Maas 1993). The parameter value of k varies with foliage characteristics, solar angle, row spacing and direction, and latitude (Thornley 1976), while the value of RUE varies dependent upon various environmental conditions as well as cultural and management practices (Foale et al. 1984; Sinclair & Horie 1989; Rosenthal & Gerik 1991; Rosenthal *et al.* 1993; Milroy & Bange 2003). Given that the value of k used in EPIC (-0.65) is representative of crops with narrow row spacing (Williams et al. 1989), the present study employed various RUE values to EPIC for simulating cotton lint yield (Fig. 8). In parameterization, as the empirical function will not necessarily produce accurate results for all possible conditions, the modeller selects the empirical functions that will result in sufficient accuracy for conditions likely to be experienced in the application of the model (Maas 1993). As the present simulation results show that the parameters used did not necessarily reproduce the field conditions, the various RUE values were objectively employed to explore the feasible range of the parameter value to fit to the measured lint yield. While the RUE values of  $2 \cdot 3 - 2 \cdot 7$  g/MJ can be applied to reproduce the cotton growth within the standard error range, the simulated lint yield with RUE 2.5 g/ MJ closely agreed with the measured lint yield. Therefore, it is considered that the RUE value of 2.5 g/MJ is suitable to reproduce the measured field conditions.

Daily ETc rates were in general agreement between the measured and simulated values and the variations of daily cumulated ETc were within an acceptable range. In-season differences among ETc methods varied, possibly due to inexact simulation growth curves or growth stage specific crop coefficients. The validation result demonstrates that the EPIC model using the RUE estimate can reproduce the field conditions of cotton in South Texas. Previously, Williams et al. (1989) reported that EPIC could accurately simulate crop responses to irrigation at locations in the western USA. More recently, Ko et al. (2007) verified that EPIC could be employed to simulate crops under various irrigation managements in the conditions of South Texas. In addition, the model has successfully been calibrated elsewhere in the world, such as China (Huang et al. 2006) and France (Cabelguenne et al. 1990).

EPIC has been verified as a suitable model for simulating long-term average crop yields. However, further efforts with intense investigation of the other parameters for the model are needed to adequately simulate yield in particular low- and high-yielding years, as shown in some of the farm field data for the present study as well as found in previous studies by Bouzaher *et al.* (1993) and Martin *et al.* (1993). As Kiniry *et al.* (1995) pointed out, overestimation of the amount of plant-available water at field capacity can cause EPIC to overestimate yield in dry years. It is considered helpful to measure maximum depth of

water extraction using appropriate cultivars in the region.

The k (-0.63) and RUE (2.5 g/MJ) values of cotton were determined based on the field experiment and employed the values to reproduce the field conditions using EPIC, which simulated the variability in lint yields with r of 0.86 and RMSE of 0.22 t/ha. The main conclusion from the present work is that appropriate parameter estimates, including RUE, are critical to reproduce the field conditions of a crop. The results also show that with appropriate parameter estimation, EPIC can give reasonable meanyield simulations for crops of interest in the South Texas conditions.

This study is a partial outcome of the Precision Irrigators Network (PIN) project, funded by Texas Water Development Board (TWDB: Project No. 0603580596) and Rio Grande Basin Initiative (RGBI: Grant No. 2005-34461-15661). The authors would like to express their appreciation to Dr Gerik and his group for their supports in calibrating the EPIC model. We thank Brian Trees and Amy Wentz for taking field measurements and Texas Water Resources Institute (TWRI) for administrative project assistance. We would also like to thank the anonymous editor and reviewers for the valuable comments.

## REFERENCES

- ASCE-EWRI (2005). The ASCE Standardized Reference Evapotranspiration Equation. Environment and Water Resources Institute (EWRI) of ASCE, Standardization of Reference Evapotranspiration Task Committee Final Report. Available online at http://www.kimberly.uidaho.edu/water/asceewri/ascestzdetmain2005.pdf (verified 12 November 2008).
- Bell, M. J., Wright, G. C. & Harch, G. R. (1993). Environmental and agronomic effects on the growth of four peanut cultivars in a subtropical environment I. Dry matter accumulation and radiation use efficiency. *Experimental Agriculture* **29**, 473–490.
- Bouzaher, A., Shogren, J. F., Holtkamp, D., Gassman, P., Archer, D., Lakshminarayan, P., Carriquiry, A. L. & Reese, R. (1993). Agricultural Policies and Soil Degradation in Western Canada: An Agro-ecological Economic Assessment (Report 2: The environmental Modeling System). Technical Report 3/93. Ottawa, ON, Canada: Agricultural Canada, Policy Branch.
- CABELGUENNE, M., JONES, C. A., MARTY, J. R., DYKE, P. T. & WILLIAMS, J. R. (1990). Calibration and validation of EPIC for crop rotation in southern France. *Agricultural Systems* 33, 153–171.
- CHARLES-EDWARDS, D. A., DOLEY, D. & RIMMINGTON, G. M. (1986). Modelling Plant Growth and Development. Sydney: Academic Press.
- Foale, M. A., Wilson, G. L., Coates, D. B. & Haydock, K. P. (1984). Growth and productivity of irrigated *Sorghum bicolor* (L. Moench) in Northern Australia. II. Low solar altitude as a possible seasonal constraint to

- productivity in the tropical dry season. *Australian Journal of Agricultural and Resource Economics* **35**, 229–238.
- Gallagher, J. N. & Biscoe, P. V. (1978). Radiation absorption, growth and yield of cereals. *Journal of Agricultural Science, Cambridge* **91**, 47–60.
- HARGREAVES, G. H. & SAMANI, Z. A. (1985). Reference crop evapotranspiration from temperature. Applied Engineers in Agriculture 1, 96–99.
- HOWELL, T. A. & MUSICK, J. T. (1985). Relationships of dry matter production of field crops to water consumption. In Les Besoins en équ des Cultures. Conférence Internationale, Paris, 11–14 September 1984. pp. 247–269. Paris: INRA.
- HOWELL, T. A., MEEK, D. W. & HATFIELD, J. L. (1983). Relationship of photosynthetically active radiation to shortwave radiation in the San Joaquin valley. *Agricultural Meteorology* 28, 157–175.
- HUANG, M., GALLICHAND, J., DANG, T. & SHAO, M. (2006). An evaluation of EPIC soil water and yield components in the gully region of Loess Plateau, China. *Journal of Agri*cultural Science, Cambridge 144, 339–348.
- Huschke, R. E. (1959). Glossary of Meteorology. Boston, MA: American Meteorology Society.
- JACKSON, B. S. & HEARN, G. F. (1990). COTTAM: A Cotton Plant Simulation Model for an IBM PC Microcomputer. Texas Agricultural Experiment Station. Miscellaneous Publication MP-1685.
- KINIRY, J. R., JONES, C. A., O'TOOLE, J. C., BLANCHET, R., CABELGUENNE, M. & SPANEL, D. A. (1989). Radiation-use efficiency in biomass accumulation prior to grain filling

for five grain-crop species. *Field Crops Research* **20**, 51–64.

- Kiniry, J. R., Major, D. J., Izaurralde, R. C., Williams, J. R., Gassman, P. W., Morrison, M., Bergentine, R. & Zentner, R. P. (1995). EPIC model parameters for cereal, oilseed, and forage crops in the northern Great Plains region. *Canadian Journal of Plant Science* 75, 679–688.
- KINIRY, J. R., TISCHLER, C. R. & VAN ESBROECK, G. A. (1999). Radiation use efficiency and leaf CO<sub>2</sub> exchange for diverse C<sub>4</sub> grasses. *Biomass and Bioenergy* 17, 95–112.
- KINIRY, J. R., SIMPSON, C. E., SCHUBERT, A. M. & REED, J. D. (2005). Peanut leaf area index, light interception, radiation use efficiency, and harvest index at three sites in Texas. Field Crops Research 91, 297–306.
- Ko, J., Maas, S. J., Lascano, R. J. & Wanjura, D. (2005). Modification of the GRAMI model for cotton. *Agronomy Journal* 97, 1374–1379.
- Ko, J., PICCINNI, G., STEGLICH, E., GERIK, T. J., MAREK, T., HOWELL, T. & KEMANIAN, A. (2007). Using EPIC simulation model to manage irrigated crops. ASA-CSSA-SSA 2007 International Annual Meetings, New Orleans, LA, November4–8. CD-ROM.
- MAAS, S. J. (1993). Parameterized model of gramineous crop growth: I. leaf area and dry mass simulation. *Agronomy Journal* 85, 348–353.
- MARTIN, S. M., NEARING, M. A. & BRUCE, R. R. (1993). An evaluation of the EPIC model for soybeans grown in Southern Piedmont soils. *Transactions of the American Society of Agricultural Engineers* 36, 1327–1331.
- МЕЕК, D. W., HATFIELD, J. L., HOWELL, T. A., IDSO, S. B. & REGINATO, R. J. (1984). A generalized relationship between photosynthetically active radiation and solar radiation. Agronomy Journal 76, 939–945.
- MILROY, S. P. & BANGE, M. P. (2003). Nitrogen and light responses of cotton photosynthesis and implications for crop growth. *Crop Science* 43, 904–913.
- Monsi, M. & Saeki, T. (1953). Über den Lichtfaktor in den Pflanzengesellschaften und seine Bedeutung für die Stoffproduktion (On the factor light in plant communities and its importance for matter production). *Japanese Journal of Botany* 14, 22–52.

- Monteith, J. L. (1965). Evaporation and the environment. In The State and Movement of Water in Living Organisms, XIX Symposium, Society for Experimental Biology, Swansea, pp. 205–234. Cambridge: Cambridge University Press.
- Monteith, J. L. (1977). Climate and the efficiency of crop production in Britain. *Philosophical Transactions of the Royal Society of London B* **281**, 277–294.
- Morgan, C. L. S., Norman, J. M. & Lowery, B. (2003). Estimating plant-available water across a field with an inverse yield model. *Soil Science Society of America Journal* 67, 620–629.
- ROSENBERG, N. J., BLAD, B. L. & VERMA, S. B. (1983). Microclimate: The Biological Environment, 2nd edn. New York: John Wiley and Sons.
- ROSENTHAL, W. D. & GERIK, T. J. (1991). Radiation use efficiency among cotton cultivars. *Agronomy Journal* 83, 655–658.
- ROSENTHAL, W. D., GERIK, T. J. & WADE, L. J. (1993). Radiation-use efficiency among grain sorghum cultivars and plant densities. *Agronomy Journal* 85, 703–705.
- SINCLAIR, T. R. & HORIE, T. (1989). Leaf nitrogen, photosynthesis, and crop radiation use efficiency: a review. *Crop Science* 29, 90–98.
- THORNLEY, J. H. M. (1976). Mathematical Models in Plant Physiology. London: Academy Press.
- TOLLENAAR, M. & BRUUSEMA, T. W. (1988). Efficiency of maize dry matter production during periods of complete leaf area expansion. *Agronomy Journal* 80, 580–585.
- WANG, X., WILLIAMS, J. R., IZAURRALDE, R. C. & ATWOOD, J. D. (2004). Sensitivity and uncertainty analyses of crop yields and soil organic carbon simulated with EPIC. Transactions of the American Society of Agricultural Engineers 48, 1041–1054.
- WILLIAMS, J. R., JONES, C. A. & DYKE, P. T. (1984). A modelling approach to determining the relationship between erosion and soil productivity. *Transactions of the American Society of Agricultural Engineers* 27, 129–144.
- WILLIAMS, J. R., JONES, C. A., KINIRY, J. R. & SPANEL, D. A. (1989). The EPIC crop growth model. *Transactions of the American Society of Agricultural Engineers* 32, 497–511.